## **INVITATION FOR BID**

## **ADDENDUM #1**

**Questions and Clarifications** 

Wrecker Tow Truck IFB #FED2019-08-01

**TO:** Prospective Bidders

**FROM:** Martha Howarter, Director of Federal Programs

**DATE:** October 30, 2019

**SUBJECT:** Addendum No. 1 – Questions and Clarifications

The following is included as part of Addendum No.1 and supersedes the language/requirements set forth in the original "Invitation for Bid".

## **ADDENDUM #1 – Questions and Clarifications**

#	Questions submitted or asked	Response from GPMTD
1	Page 33	Revised Language:
	2-6.23 Miscellaneous Components	8. The front bumper shall be a steel
	8. The front bumper shall be Three-Fourth inch	counterweighted front bumper. Shall be capable
	(3/4") thick, Twenty-four inch (24") high and	of adding additional ballast to achieve the
	eighty-one inch (81") in length and be	required front axle weight to achieve the front
	constructed of non-skid steel plate. Hardware	axle lift off points described elsewhere. The
	required to fasten the onto the chassis frame rail	bumper shall be approximately 24" tall and 81"
	shall be SAE Grade 8 minimum. The bumper	wide. The bumper shall have a rubber cover to
	shall have a rubber cover to be suitable for use	be suitable for use as a push bumper. Hardware
	as a push bumper	used to fasten the bumper shall be Grade 8.